无纸化门口屏

▶ Feature:

1. Structural design: pure flat structure, ergonomic design, slim and beautiful, streamlined shape, excellent workmanship; high-definition display, capacitive touch, host system integrated ultra-thin design

2. Usage effect: using the latest technology projected capacitive screen, perfect 10-point touch, support handwriting and multi-point gestures; touch speed is less than 3ms, good accuracy, simple and convenient to use, easy to maintain; anti-light interference, ensure the accuracy of operation (strong light direct use as usual)

3. Good expandability: flexible configuration, can expand and install various functional accessories required by customers

4. High safety: aluminum alloy + sheet metal structure, no sharp edges, wear-resistant and anti-corrosion paint process, overall anti-riot design

5. Stable performance: advanced design concept, strict production process, stable and reliable product quality, low failure rate

6. Easy installation: automatic power on, one-time debugging, long-term stability

7. Support timed power on and off function to achieve unattended function

▶ Specification:

System version	Android 11
CPU type	RK3568, quad-core 64-bit Cortex-A55, main frequency 2.0GHz
GPU	ARM G52 2EE, supports 4K 60fps H.265/H.264/VP9 video decoding
NPU	supports 0.8T computing power
System memory	2G DDR4
Storage capacity	16GB built-in (TF card can be expanded to 128Gb)
USB	2 USB3.0 (1 USB3.0 is USB_OTG)
Audio interface output	1, up to two 8Ω 5W Dual-channel speaker output
LAN (RJ45)	1, 10M/100M/1000M adaptive Ethernet
WiFi/3G/4G/Bluetooth	Support WIFI-2.4G, BT-4.1
POE	Support POE function, support IEEE802.3af/at standard
TTL to 485 serial port	1
Back interface	Support network port and 485 serial port back output, suitable for embedded installation
Screen	15.6 inches
Effective display size	345.16×194.59 mm (16:9)
Complete machine size (width × height × thickness)	376*231*30.5 mm; packaging size (width × height × thickness) 436*344*63 mm
Bracket	wall-mounted, wall-mounted screw specification M4
Net weight (bare machine)	2.7 kg Gross weight (packaging) 3.3 kg