



► Feature:

1. Adopting aluminum alloy structure shielding design, the chassis can resist contact 4KV strong magnetic interference, dustproof, and impact-proof, stable and reliable
2. Stylish appearance, small device size, easy to install
3. The front panel is equipped with power on and restart buttons, status indicator lights, which can visually check whether the device is running normally, and quickly restart the device
4. Support Win7/10/Linux/domestic Galaxy Kylin version and other operating systems, with excellent compatibility
5. Support 1 set of 3.5MM high-fidelity audio input and output interfaces
6. Support 4K high-definition synchronous dual display, one standard HDMI and one VGA signal output, support adaptive projection resolution, support forced output resolution, and facilitate the retrieval and display of multi-adaptive images
7. Support one HDMI signal input, and the external signal broadcasts the image to all conference terminals in real time through this interface and displays it synchronously
8. The core is the domestic Zhaoxin KX-U6780 eight-core processor, equipped with domestic BIOS, loaded with domestic operating system and domestic basic application software, to achieve independent control, safe and reliable domestic computer system platform
9. Rich interfaces, 1*LAN, 7*USB, 1*remote power on/off (USB), 1*VGA, 1*HDMI, 2 sets of 3.5MM Audio

► Specification:

Processor	Zhaoxin KX-U6780, octa-core, 2.5GHz
Chipset	integrated chipset N/A
Running memory	2*SO-DUMM Slot, DDR4 2666/2400, up to 32G, standard 1*8G DDR4 2666 notebook memory
BIOS	BYO BIOS, 64MbFlash ROM
Display	integrated graphics card HDMI+VGA
Video capture port	HDMI
Network interface	standard 1*RJ45 10/100/1000Mbps adaptive network port (Realtek), optional built-in wireless WIFI, support remote wake-up
Hard disk specifications	128G PCIe SSD (standard), support 1*M.2 2280 PCIe SSD
I/O interface	1*LAN, 1*HDMI, 1*VGA, front 4*USB (1*USB3.0, 2*USB2.0, 1*power on/off USB), rear 4*USB (2*USB3.0, 2*USB2.0), 2*Line out, 1*DC power supply
Working temperature	0°C~60°C, storage temperature: -10°C~60°C, working humidity: 5%~95% relative humidity, no condensation
Power supply	DC19V power input with 120W power adapter
ESD	contact 4Kv, air gap 6Kv strong electromagnetic interference
Box material	high-quality industrial hardware
Installation method	desktop
Operating system	default Galaxy Kylin system, optional UOS/Windows/Linux
Weight	1.4Kg
Dimensions	194L*185W*40H (mm)
Vibration resistance	in line with GB/T2423.10 standard