

Portable Display FT-PM156A





Feature:

- 1. Multifunctional portable display, with hidden bracket, minimalism;
- 2. HDR pure picture quality, showing more details, more layered light and dark contrast, better color expression;
- 3. Provides high-accuracy touch function, accurate touch and high-response touch experience;
- 4. Integrated bracket design: The body comes with an invisible bracket, and the viewing angle can be easily adjusted by 90° as you move;
- 5. 3ms response without delay, optimized dynamic clarity to keep the picture stable, clear and without residual image
- 6. Built-in dual speakers make the sound clearer and brighter
- 7. Rich interface configuration: standard HDMI interface is compatible with more devices, and the full-function Type-C interface is directly connected to

mobile phones, computers, and notebooks

Specification:

- 1. Display: 15.6 inches 1920*1080P 50-60Hz
- 2. HDMI input: standard HDMI1.4 (HDCP1.4) 1920*1080P 50-60Hz
- 3. Type-C1 input: Type-C1 (USB-C full function) 1920*1080P 50-60Hz
- 4. Type-C1 input: Type-C2 (USB-C full function) 1920*1080P 50-60Hz
- 5. USB input: USB-A 2.0 built-in USB HUB 2.0 (connect mouse and keyboard)
- 6. Auido output: Audio 3.5mm standard port (headphone/amplifier output)
- 7. Button control: 3 buttons (power on/off, plus, minus)
- 8. Touch menu: touch control menu
- 9. Built-in speaker: stereo 2.0 8Ω1W * 2
- 10. Brightness adjustment: 20-250cd/mPWM dimming
- 11. Contrast adjustment: support
- 12. Scenario mode switching: 6 preset modes
- 13. Dynamic contrast: changes according to the displayed content scene
- 14. Sharpness adjustment: 1-4 levels
- 15. Color temperature adjustment: preset 9300K 6500K 5800K user defined, default 7500K
- 16. Color adjustment: support RGB simultaneous adjustment
- 17. Saturation adjustment: support
- 18. Low blue light adjustment: 1-10 levels
- 19. Color gamut mode selection: 4 preset modes
- 20. Volume control: 0-10 levels
- 21. Mute switch: support
- 22. Language selection: 10 preset languages
- 23. HDR: support
- 24. Free sync: support
- 25. Signal source channel switching: support switching when input simultaneously
- 26. Power input specification: 100V-240V 50/60HZ

