

Square pole conference unit

T3-AS01



Product Features

1. All-metal square pole microphone design, high sensitivity, high-end and solemn appearance

2. Digital audio transmission technology, realizes audio signal transmission and processing, and resists mobile phone,

electromagnetic and high-frequency interference

3. The microphone and the host are connected in a 6-core T-type cable in a "hand-in-hand" manner. The unit comes with a tail line, which can effectively prevent the plug from falling off

4. It adopts a gold-plated film high-fidelity microphone head, cardioid directional sound reception effect, and better sound quality

5. The microphone has a red indicator light to display the working status of the unit, speaking/off

6. Customized chairman unit configuration function, according to on-site needs, any unit can be customized as a chairman unit, and there is no limit on the number of chairman units

7. With voice control function, the microphone can be automatically turned on after speaking

8. The unit is uniformly powered by the host and supports hot plugging of microphones

| Туре | Cardioid | Frequency response | 60Hz~16KHz |
|-------------------|--|---------------------------|---------------|
| Input impedance | 1ΚΩ | Dynamic range | 103 dB (1KHz) |
| Sensitivity | -35dBV/Pa | Signal-to-noise ratio | 70dB |
| THD | 0.1% | Maximum power consumption | 1.5W |
| Weight | 710g | | |
| Connection method | Conference six-core dedicated connection cable | | |
| Dimensions (mm) | length * width * height microphone rod 209x32x71; base 138x98x55 | | |

Specifications