



► Feature:

1. Designed based on the principle of acoustic interference
2. Adopting UHF digital wireless communication frequency band, combined with the digital conference system architecture, independently developed wireless anti-interference audio communication technology, ensuring the stability of the system
3. Communication frequency band: 650MHz~700MHz data communication, 5 groups of communication frequency bands are optional, and they do not interfere with each other
4. The unit is equipped with a 6000mAh lithium polymer battery, the continuous speaking time can reach 48 hours, ultra-long standby, and 1A charging current can be quickly charged
5. With volume adjustment and battery power indicator buttons, you can easily adjust the volume and view the current battery power
6. Customized chairman machine configuration function, you can temporarily define any unit as the chairman unit according to the needs of the site
7. Made of zinc alloy die-casting, it has good stability and shock resistance, and the bottom is equipped with shockproof foot pads to effectively prevent the noise caused by desktop vibration
8. The microphone has a simple and elegant appearance design, and the microphone pole pickup end is decorated with LED indicator lights, making the microphone show a simple and solemn conference equipment style
9. One-button switch microphone, simple and atmospheric, very suitable for use in speeches, teaching, meetings, reports, churches and other occasions
10. According to the conference control software purchased by the user, a variety of conference management functions can be realized

► Specification:

Output frequency response	20-20KHz
Signal-to-noise ratio	>78 dB
Working voltage	24V DC
Total harmonic distortion	≤ 0.05%
Maximum power consumption	1.5W
Shell material	Zinc/aluminum alloy
Weight	0.89kg
Color	Base: dark blue ; Microphone rod: black
Dimensions (length * width * height mm)	Base: 138*98*54 Mic rod: φ21.5*294 (without windshield)
Microphone parameters	
Standard spare parts	sponge windshield
Directional characteristics	super directional
Mic rod	4-pin XLR female head Mic rod(with LED indicator)
Sensitivity	-33 dB
Frequency response	20-20KHz
Output impedance	680Ω
Connection socket between microphone and base	M16 aviation female core-4Ppin*1 M16 aviation male core-4Ppin*1