



► Specification:

Rated power (THD = 1%, continuous sine 1kHz, typical value)	8Ω/stereo: 2×3000W、4Ω/stereo: 2×5100W、2Ω/stereo: 2×8600W
Rated power (THD = 1%, continuous sine 1kHz, typical value)	16Ω/bridge: 1×6000W、8Ω/bridge: 1×10200W、4Ω/bridge: 1×17340W
RMS output voltage (THD = 1%, 1kHz)	154.9V
Input sensitivity (rated output power, 1kHz)	Optional: 41dB, 38dB, 35dB, 32dB
THD+N	typical value: 0.01% (10% rated output power, 1kHz, 8Ω)
Crosstalk suppression	≥90dB (lower than rated power, 20Hz-1kHz, 8Ω)
Frequency response	Typical value: +0dB, -0.5dB (10% rated output power, 20Hz-20kHz, 8Ω)
Input impedance	20kΩ (balanced), 10kΩ (unbalanced)
Damping factor	Typical value: 3500 (8Ω, 20Hz-200Hz)
Signal-to-noise ratio	≥105dB (A-weighted, 20Hz-20kHz, 8Ω)
Power supply requirements	90~260VAC, 50/60Hz
Protection function	power supply undervoltage protection, amplifier output DC protection, overheating protection, temperature power control, overload power control
Dimensions (W×H×D)	483×45×465
Net weight	13kg
Product static power consumption	150
Product dynamic power consumption	1191.7