



► Specification:

Rated power (THD = 1%, continuous sine 1kHz, typical value)	8Ω/stereo: 2×650W、4Ω/stereo: 2×1100W、2Ω/stereo: 2×1870W
Rated power (THD = 1%, continuous sine 1kHz, typical value)	16Ω/bridge: 1×1300W、8Ω/bridge: 1×2200W、4Ω/bridge: 1×3740W
RMS output voltage (THD = 1%, 1kHz)	72.1V
Input sensitivity	Optional: 38dB, 35dB, 32dB, 29dB
THD+N	typical value: 0.01% (10% rated output power, 1kHz, 8Ω)
Crosstalk suppression	≥90dB (below rated power, 20Hz-1kHz, 8Ω)
Frequency response	Typical value: +0dB, -0.5dB (10% rated output power, 20Hz-20kHz, 8Ω)
Input impedance	20kΩ (balanced), 10kΩ (unbalanced)
Damping factor	Typical value: 3500 (8Ω, 20Hz-200Hz)
Signal-to-noise ratio	≥105dB (A-weighted, 20Hz-20kHz, 8Ω)
Power requirements	90~260VAC, 50/60Hz
Protection functions	power undervoltage protection, amplifier output DC protection, overheating protection, temperature power control, overload power control
Dimensions	483×45×370 (W×H×D)
Net weight	9kg
Static power consumption	60
Dynamic power consumption	285.7