



Specification:

Rated power (THD = 1%, continuous sine 1kHz, typical value)	8Ω/stereo: 4×450W、4Ω/stereo: 4×765W、2Ω/stereo: 4×1300W
Rated power (THD = 1%, continuous sine 1kHz, typical value)	16Ω/bridge: 2×900W、8Ω/bridge: 2×1530W、4Ω/bridge: 2×2600W
RMS output voltage (THD = 1%, 1kHz)	60.0V
Input sensitivity	Selectable 35dB, 32dB, 29dB, 26dB
THD+N: typical value	0.01% (10% rated output power, 1kHz, 8Ω)
Crosstalk suppression	≥90dB (below rated power, 20Hz-1kHz, 8Ω)
Frequency response	Typical value: +0dB, -0.5dB (10% rated output power, 20Hz-20kHz, 8Ω)
Input impedance	20kΩ (balanced), 10kΩ (unbalanced)
Damping factor	Typical value: 3500 (8Ω, 20Hz-200Hz)
Signal-to-noise ratio	≥105dB (A-weighted, 20Hz-20kHz, 8Ω)
Power supply requirements	90~260VAC, 50/60Hz
Protection function	power undervoltage protection, amplifier output DC protection, overheating protection, temperature power control, overload power control
Dimensions	483×45×370 (W×H×D)
Net weight	9kg
Product static power consumption	50
Product dynamic power consumption	362.5