



► Feature:

1. With 10-zone paging function
2. The audio signal adopts high-quality balanced transmission technology, with long signal transmission distance and low distortion
3. The audio signal and control signal share one transmission line, and the twisted pair is transmitted in real time
4. Four remote control zones/paging microphones can be cascaded
5. It can realize zone paging of 8 pagers, and the remote control distance can reach 1KM
6. The output volume is adjustable
7. The function buttons are made of aluminum and light-touch soft keys to control the switch
8. It has bell prompt and silent switch functions
9. It has a full-zone on/off control function, which is convenient for users to perform full-zone paging broadcasts

► Specification:

Equipment model	RH2810R
Microphone input	(MIC) MIC:600 ohms (Ω) 5mV, unbalanced
Line input	LINE:10K ohms (Ω) 0.775 (0dB), unbalanced
Line output	10k ohms (Ω) 0.775V (0 dB), unbalanced
Frequency response	MIC:100Hz~10kHz(\pm 3dB) LINE:20Hz~15kHz(\pm 3dB)
Non-linear distortion THD	<0.01% at 1kHz
Signal-to-noise ratio S/N	>70 dB
Number of controllable partitions	ten partitions 'CH1 ~ CH10'
Partition output control	any partition can be manually selected to activate
Power cord	(3×0.5 mm ²)×1.5M (standard)
Power supply	AC 220V \pm 10% 50-60Hz
Power consumption	5~10W
Machine size	78(H)×205(W)×178(D)mm
Net weight	1.84kg