



### Feature:

1. High-grade aluminum 2U black oxidized brushed panel, beautiful and elegant
2. 2-way input, 10-zone output (70V/100V audio signal).
3. 10 channel zones can be selected at will
4. 25-pin computer activation interface, 10-way alarm input
5. Background music and emergency broadcast switching do not affect each other
6. 10 output channel selection LED indication
7. DC24V and AC100~240V dual power supply, automatically switch to DC24 DC power supply when there is no AC input
8. Group A input:70V/100V, audio signal
9. Group B input:70V/100V, emergency broadcast (alarm. audio signal)

### Specification:

Channel switching capacity	500 W, audio signal
Alarm activation input	(0V) short-circuit signal, (ALARM IN)
Alarm activation output	(0V) short-circuit signal two-way, (ALARM OUT)
Power cord	(3×0.75 mm <sup>2</sup> )×1.5M (standard)
Power supply	AC 220V±10%50-60Hz
Power consumption	10~15W
Machine size	89(H)×483(W)×350(D)mm
Net weight	6.34kg
Controllable number of zones	ten zones 'CH1~CH10' (emergency broadcast (alarm) audio signal is activated and output by alarm signal)
Controlled zone output capacity	total audio signal input capacity:1 kW; each zone output can be allocated an average load capacity of 100 W