



Feature:

1. High-grade aluminum 2U black oxidized brushed panel, beautiful and elegant
2. With 16-zone paging alarm function
3. 1 microphone input, 4 remote microphone inputs, 1 line, 1 emergency input
4. Remote audio/control signal adopts high-quality balanced transmission technology
5. LED status indication for each paging channel
6. Built-in chime generator with mute function
7. 25-pin computer activation interface, low-level alarm activation output
8. Manual paging function can be performed through the buttons on the panel
9. MIC volume adjustment, output volume can be adjusted

Specification:

Microphone input (MIC)	MIC:600 ohms (Ω) 5mV, unbalanced
Line input (LINE)	10k ohms (Ω) 200mV, unbalanced
Line output	10k ohms (Ω) 0.775V (0 dB), unbalanced
Frequency response	60 Hz ~ 15k Hz (\pm 3 dB)
Non-linear distortion	THD<0.01% at 1kHz
Signal-to-noise ratio S/N	>70 dB
Alarm activation input port	one group of 'ALARM IN (CH1 ~ CH16)'
Alarm activation output port	one group of 'SWITCHING OUT (CH1 ~ CH16)'
Alarm activation	low level activation (0V)
Level selection	select 'HIGH' / 'LOW' by the ACTIVE LEVEL setting switch
Silent suppression capability	When EMC is input, MIC and LINE signals are attenuated by 0~30 dB
Power supply	AC 220V \pm 10% 50-60Hz
Power consumption	10~15W
Machine size	89(H) \times 483(W) \times 350(D)mm
Net weight	6.32kg