



Feature:

1. High-grade aluminum 2U black oxidized brushed panel, beautiful and elegant
2. Double-sided PCB board process, stronger component adhesion and more stable performance
3. Adopting a new pure copper transformer, more powerful power and higher efficiency
4. Equipped with RCA jack, XLR jack, more flexible interface
5. Equipped with 100V, 70V constant voltage output and 4~16Ω constant resistance output
6. Adjustable output volume
7. 5-unit LED display, easy to observe the working status
8. With perfect output short circuit, high temperature, overload, DC protection function
9. Cooling fan temperature control start
10. Rated output power:660W
11. Output mode:4-16 ohms(Ω) constant resistance output 70V(7.4 ohms(Ω))100V(15.1 ohms(Ω)) constant voltage output
12. Line input:10k ohms(Ω) < 1V, unbalanced
13. Line output:10k ohms(Ω) 0.775V (0 dB), unbalanced

Specification:

Frequency response	60 Hz ~ 15k Hz (±3dB)
Non-linear distortion THD	<0.5% at 1kHz, 1/3 rated output power
Signal-to-noise ratio S/N	>70 dB
Damping coefficient	200
Voltage rise rate	15V/uS
Output adjustment rate	< 3 dB, from no-signal static working state to full-load working state
Function control	one volume adjustment, one power switch
Cooling method	DC 12V FAN forced air cooling method
Indicator light	power: 'POWER' , top elimination: 'CLIP' , signal: 'SIGNAL' , protection: 'PROT' , high temperature: 'TEMP'
Protection	AC FUSE×15A AC FUSE×1, load short circuit, over temperature
Power cord	(3×1.5 mm2)×1.5M (standard)
Power supply	AC 220V ±10% 50-60Hz
Power consumption	880W
Machine size	89(H)×483(W)×366(D)mm