



Feature:

1. Analog input channels: 16
2. Analog output channels: 16
3. Processor: ADI SHARC 21489@450 MHz SIMD
4. DSP processing power: 400 MIPS, 1.6 GFLOPS
5. Sampling rate: 48 kHz, ± 100 ppm
6. THD+N: < -94 dB @17dBu
7. Input dynamic range: 110dB
8. Output dynamic range: 112dB
9. 4-channel GIPO
10. 1-channel RS232
11. 1-channel RS485
12. Built-in USB sound card, supports music playback, recording and soft video conferencing (such as: ZOOM, Tencent Conference, DingTalk Conference, etc.)
13. Bus-type AEC, tail time: 512ms, convergence rate: 60dB/S, echo cancellation amplitude: 60dB
14. Independent channel AFC (feedback suppression), using notch algorithm, transmission gain improvement: 10dB
15. Noise suppression (ANS), signal-to-noise ratio improvement of 18dB
16. 8-band British parametric equalization, providing 5 filter options: Parametric, Lowshelf, Highshelf, Lowpass, Highpass
17. Provide end-user customized operation interface, support up to 30 devices with the same interface management
18. With central control function, it can control the power supply, signal switching, environmental control, audio and other overall functions in the system, and realize one-click opening of the system functions
19. 40bit DSP floating point operation engine

Specification:

Processor	ADI SHARC 21489
Sampling rate/quantization bit	48K/24bit
Number of analog input and output channels	16 x 16
Input gain	0/6/12/18/24/30/36/42/48dB
Phantom power	+48V/10mA max
Frequency response (20~20kHz)	±0.15dB
Maximum level	+18dBu
THD+N	<-94dB @17dBu
Input dynamic range	110dB
Output dynamic range	112dB
Channel isolation @1kHz	108dB
Input impedance (balanced connection)	5.4KΩ
Output impedance (balanced connection)	600Ω
System delay	<6ms
Working power	AC 220V, 50Hz
Dimensions (WxDxH)	482 x 200 x 45mm
Shipping weight	4KG