



Feature:

1. Aluminum mesh cover, rust-proof box.
2. UL94V-0 flame retardant grade material (optional).
3. 4*3 inch high-performance ferrite drive unit.
4. UV waterproof dip coating, IPx4 waterproof grade, can be installed indoors and outdoors (optional).
5. Optional intelligent installation accessories, with level device, quick-release handle device, shockproof rubber pad.
6. The array sound column speaker adopts a streamlined design, beautiful and practical appearance, suitable for sound reinforcement in various architectural spaces, with beautiful sound quality.
7. The sound column speaker adopts ABS plastic mixed with glass fiber to strengthen the cabinet, which is sturdy and durable.
8. The circular waveguide hole in the front and the damping port at the rear of the cabinet form a unique low-frequency heart-shaped diffusion, with crisp and pleasant treble, natural and thick sound, and full bass.

Specification:

Drive unit	4x3 ferrite
Cone material	pulp coating
Impedance	8Ω
Rated power	100W (400W, PEAK)
SPL (1W/1m)	95dB
Maximum SPL (1W/1m)	115dB
Frequency response	150Hz~14kHz, -6dB 80Hz~20kHz, -10dB
Shell material	ABS plastic + fiberglass
Grille material	aluminum
Diffusion angle (-6dB)	vertical > 20°, horizontal > 120°
Connection interface	red and black crimping clamp
Mounting hole	10 M6
Mounting system	smart mounting bracket/embedded mounting bracket
Color	black/white (optional)
Dimensions (height × width × depth)	530x100x150mm
Product net weight	3.80kg
Package weight	5.08kg