



► Feature:

| Product Features | |
|---------------------------------|---|
| 1. HDMI & VGA Output | Simultaneous output of identical content through HDMI and VGA, with adjustable resolutions. |
| 2. Mixed Display | Supports mixed display from computers and mobile devices. |
| 3. Multi-device Display | Simultaneous display of multiple mobile devices. |
| 4. Automatic Detection | Detects multiple receivers on the same network for screen mirroring. |
| 5. Resolution Adjustment | Allows modification of resolution and aspect ratio during screen mirroring. |
| 6. Device Info Display | Displays username and type on the connected display. |
| 7. Routing Functionality | Receiver device includes routing functionality (wired or wireless). |
| 8. Internet Access | Mobile devices can screen-mirror while staying online. |
| 9. Sound-sharing Modes | Four modes, ensuring no audio mixing during multi-screen sharing. |
| 10. Reverse Control | Supports mouse and 16-point touch reverse control. |
| 11. Customization | Customizable boot/standby screen, web interface, frequency, and channel. |
| 12. WiFi and Password | Allows customization of WiFi name and password. |

► Specification:

| | |
|-----------------------------------|-------------------|
| 1. Video Input Resolution | 4K / 3840×2160 |
| 2. Video Output Resolution | 1080p / 1920×1200 |
| 3. Frame Rate | Up to 30 fps |

| | |
|---|---|
| 4. Wireless Transmission Distance | Up to 30 meters (line of sight) |
| 5. Wireless Frequency Band | 2.4 GHz or 5 GHz (default: 5 GHz) |
| 6. Wireless Encryption Protocol | WPA2-PSK |
| 7. Aspect Ratio | 4:3 / 16:9 / 16:10 |
| 8. Simultaneous Display Sources | 2 channels |
| 9. Connected Source Devices | Up to 16 devices |
| 10. Audio Output | 44.1 kHz / 16-bit stereo via HDMI and 3.5mm analog audio output |
| 11. Wireless Transmission Protocol | IEEE 802.11ac / 802.11n |
| 12. Wireless Transmission Rate | Up to 867 Mbps |
| 13. Available Channels | 9 (5G) / 11 (2.4G) |
| 14. Transmission Latency | Average latency <100 ms |
| 15. Power Supply / Consumption | Host: 12V / 1A, 5W; Button: 5V / 500mA, 1.5W |
| 16. Operating Temperature | +5°C to +40°C |
| 17. Storage Temperature | -20°C to +60°C |
| 18. Humidity | 0–90% relative humidity (non-condensing) |
| 19. Standard Accessories | 2 transmitters, power supply, storage case, antenna |
| 20. Hardware Interfaces | VGA, HDMI, Network, Standby Switch, 3.5mm Audio, USB, 12V Power Input, Security Lock Hole |
| 21. OS Compatibility | Windows 7/8.1/10, macOS X 10.10+, iOS 9+, Android 5.0+ (requires app installation, ESHOW) |