



Feature:

1. Top-grade gold film high-fidelity microphone capsule, super-directional sound receiving effect, better sound quality.
2. Integrated microphone rod
3. Built-in high-performance CPU, faster processing speed, better sound quality
4. The effective sound receiving angle of 100° can prevent interference from adjacent microphones and suppress howling
5. With the video switcher and camera, the camera automatic tracking function can be realized after using the computer preset
6. Customized chairman unit configuration function, according to the needs of the site, any unit can be temporarily defined as the chairman unit, and there is no limit on the number of chairman units
7. The system has an automatic repair function and supports hot plugging of lines

Specification:

Frequency response	40Hz-16KHz
Signal-to-noise ratio	>74 dB
Dynamic range	>108 dB(1 KHz)
Total harmonic distortion	<0.05%
Maximum power consumption	1.5W
Headphone volume	10mW
Headphone load	>16 Ω
Headphone output interface	Ø 3.5 mm stereo jack
Shell material	Zinc-aluminum alloy
Connection method	FionTu conference six-core dedicated connection cable
Color	Brown
Dimensions (mm) length*width*height	Microphone rod:200*34.5*23, base:138*98*54
Microphone parameters	
Microphone head	14mm diameter gold-plated condenser microphone head
Directional characteristics	Supercardioid
Sensitivity	-28 dB
Frequency response	30Hz-18KHz
Input impedance	2.2KΩ
Maximum sound pressure level	130 dB (THD<3%)
Equivalent noise	25 dB-A
Cable parameters	
Diameter	5.5mm
Wire core	6 cores
Shielding	winding + aluminum foil
Wire length	2 meters + 1 meter