



Feature:

1. Adopt analog dual backup system design, one phantom microphone audio channel, one button control speech audio channel, so as to ensure the system has higher reliability
2. Top gold film high-fidelity microphone sound head, super directional sound pickup effect, better sound quality
3. Microphone connected to 48V microphone preamplifier power supply component
4. Effective sound pickup angle 100° can prevent interference from adjacent microphones and suppress howling
5. Low impedance balanced audio output
6. Microphone adjustable elevation angle -50° to 45° (horizontal)
7. Made of zinc/aluminum alloy, anodized process, CNC precision processing high gloss edge, novel appearance, simple and generous
8. Microphone panel can be customized with silk screen or laser LOGO/pattern

Specification:

Pickup microphone head	14mm diameter gold-plated capacitor microphone head * 2
Directional characteristics	Supercardioid
Sensitivity	-28 dB
Frequency response	30Hz-18KHz
Output impedance	<200Ω
Maximum sound pressure level	130 dB (THD<3%)
Signal-to-noise ratio	>74 dB
Total harmonic distortion	<0.05%
Equivalent noise	25 dB-A
Dynamic range	>108 dB(1 KHz)
Phantom power supply	48V DC
Maximum power consumption	0.6W
Shell material	Zinc/aluminum alloy
Connection method	Audio cable-2 core with shielding
Weight	1.1kg
Color Base	dark blue; Mic rod: silver
Dimensions (mm) length*width*height	Mic rod: 200*34.5*23, base: 138*98*54