



Feature:

1. Top-grade gold film high-fidelity microphone capsule, super directional sound pickup effect, better sound quality
2. Microphone connected to 48V microphone preamplifier power supply component
3. Effective sound pickup angle of 100° can prevent interference from adjacent microphones and suppress howling
4. Low-impedance balanced audio output
5. Microphone adjustable elevation angle -50° to 45° (horizontal)
6. Made of zinc/aluminum alloy, anodized process, CNC precision processing high-gloss edge, novel appearance, simple and generous
7. Microphone panel can be customized with silk screen or laser LOGO/pattern

Specification:

Pickup microphone capsule	14mm diameter gold-plated condenser microphone capsule
Directional characteristics	Supercardioid
Sensitivity	-28 dB
Frequency response	30Hz-18KHz
Output impedance	<200Ω
Maximum sound pressure level	130 dB (THD<3%)
Signal-to-noise ratio	>74 dB
Total harmonic distortion	<0.05%
Equivalent noise	25 dB-A
Dynamic range	>108 dB(1 KHz)
Phantom power supply	48V DC
Maximum power consumption	0.3W
Shell material	Zinc/aluminum alloy
Connection method	Audio cable-2 core with shielding
Weight	1kg
Color	Qiang blue
Dimensions (mm) length*width*height	Mic rod: 200*34.5*23, base: 138*98*54