



► Feature:

1. Top-grade gold film high-fidelity microphone capsule, super-directional sound pickup effect, better sound quality
2. Built-in high-performance CPU, faster processing speed, better sound quality
3. Effective sound pickup angle of 100° can prevent interference from adjacent microphones and suppress howling
4. Round high-resolution display touch screen: supports dynamic clock display, call service, receive messages, display pictures, adjust volume, customize interface, sign-in, voting, voting, election, scoring and other functions
5. Add PC software function, optional 4-input 2-output 3G-SDI high-definition seamless switching matrix, support a variety of proprietary software modules
6. Customized chairman machine configuration function, according to the needs of the site, temporarily define any unit as the chairman unit, no limit on the number of chairman units
7. The system has an automatic repair function and supports hot plugging of the line
8. The microphone can be adjusted from -50° to 45° (horizontal)
9. Made of zinc/aluminum alloy, anodized process, CNC precision processing high-gloss edge, novel appearance, mainly used in high-end conferences and other professional occasions

► Specification:

Output frequency response	20Hz-20KHz
Signal-to-noise ratio	> 74 dB
Dynamic range	> 108 dB(1 KHz)
Total harmonic distortion	<0.05%
Maximum power consumption	2.3W
Phantom power	48V DC
Headphone volume	10mW
Headphone load	> 16 Ω
Screen	Round 50mm diameter capacitive touch screen
Headphone output interface	Ø 3.5 mm stereo jack
Screen resolution	480*480
Storage	TF card
Shell material	Zinc/aluminum alloy
Connection method	FionTu conference six-core dedicated connection cable
Weight	0.95kg
Color Base	brown
Microphone rod	silver
Dimensions (mm) length*width*height	Mic rod:200*34.5*23, base:138*98*54
Microphone parameters	
Microphone capsule	14mm diameter gold-plated condenser capsule
Directional characteristics	Supercardioid
Sensitivity	-28 dB
Frequency response	20Hz-20KHz
Input impedance	2.2KΩ
Maximum sound pressure level	130 dB (THD<3%)
Equivalent noise	25 dB-A