



► Specification:

Lamp beads	SMD/1515
Scanning method	40S
Pixel pitch	2mm
Pixel structure	1R1G1B
Pixel density	250000/m2
Module resolution	160 (W) * 80 (H)
Module size	320mm*160mm
Main parameters	
Visible viewing distance	≥2m
Horizontal viewing angle	≥160° Vertical viewing angle:≥160°
Color temperature	1000K-10000K adjustable
Whole screen flatness	≤0.2mm
Single point brightness and color correction	Yes
Brightness uniformity	≥99%
White balance brightness	≥800cd/m ²
Function	De-blanking drive protection circuit and high grayscale high refresh design
Contrast	≥10000:1
Refresh rate	≥3840Hz
Frame frequency	≥60HZ
Grayscale level	65536
Driving mode	constant current
Control mode	synchronous
Control distance	network cable:100 meters, optical fiber:10 kilometers
Signal interface	RJ45 interface
Brightness adjustment range	0 to 100 stepless adjustment
Continuous working time	≥72 hours
Typical life	100000 hours
Protection level	IP5X
Installation box specifications	magnetic installation
Electrical parameters	

Magnetic mounting with small pitch

SP2000E-M00A

Working voltage	DC:4.2-5V
Power supply requirements	AC:220× (1±10%) V, 50× (1±5%) Hz
Maximum power consumption	≤650 W/m ²
Average power consumption	≤217 W/m ²
Environmental parameters	
Storage temperature range	-20 °C to 60 °C
Operating temperature range	-20 °C to 50 °C
Operating humidity range	10%- 80% RH without condensation