



Feature:

1. The touch ultra-thin high-definition display screen is integrated with the lifter, with no exposed connection wires, no connection back plate, and no exposed screws, ensuring that the lifting display touch screen is beautiful and elegant overall
2. With integrated microphone lift, the microphone lift has an automatic straightening function, and can rise and fall freely regardless of the position of the microphone rod bending
3. The microphone supports the custom chairman unit configuration function, and any unit can be temporarily defined as the chairman unit according to the needs of the site. There is no limit on the number of chairman units
4. The front main screen adopts a 15.6-inch 100% full color gamut IPS full-viewing angle ultra-thin high-definition LCD screen design, using the original latest full-fit curved screen technology to minimize the black border, high resolution (1920*1080 p. Bare screen, response time: 5ms)
5. The back uses an integrated 10.1-inch high-definition LCD screen for table card display function; display name information, position and unit name
6. The display frame is an integral aluminum alloy, which is sandblasted and oxidized after one-time CNC precision machining. The display area micro-frame is $\leq 4.8\text{mm}$, which increases the visible area by 10% compared to the 16:9 full-screen picture, and the screen-to-body ratio is not less than 92%
7. The front screen display area is covered by 2mm tempered protective glass, and the single-point impact strength of the surface is 5 times that of ordinary glass. The visual angle is bright and wide, and there is no obvious black edge appearance
8. Touch screen technology: the inner side is a multi-point capacitive touch screen (touch capacitive/Modular 7 level, 10-point touch, sensitivity ≤ 2 ounces, touch response time $\leq 3\text{ms}$., supports full-screen touch, can slide, drag, zoom to view meeting materials)
9. The whole machine adopts ultra-thin appearance design, the surface is treated with anodized sandblasting coloring process, exquisite and beautiful, the whole machine chassis is made of high-grade anodized aluminum alloy
10. The display panel adopts Multi-Touch multi-point touch technology, touching any point can withstand more than 5,000 10,000 touches
11. The desktop panel has a USB interface, and you can browse or upload files by connecting a USB flash drive
12. The terminal switch power button supports LED light-transmitting display. It is off when the device is turned off, and LED light-transmitting when the device is operating normally. It can effectively identify the operation of the device in various dim environments
13. Panel buttons: with up, down, stop buttons, forward and backward adjustment buttons, all of which use photoelectric touch buttons
14. Supports the emergency stop function: when the lift encounters resistance during operation and cannot be lifted, the motor will automatically stop running to avoid damage to the motor or accessories

15. The lifting speed time is optional, the default lifting one-way time is within 8s, and it can be selected within 4S
16. Support dual-channel signal input/switching: analog VGA and digital HDMI interfaces, which can be compatible with and automatically identify valid signals at the same time, independently connect the input signal source, HDMI signal and VGA high-definition signal can meet the dynamic display of full HD, and support the screen automatically enters power saving mode when there is no signal input
17. All lines All adopt standard double insulation and safety grounding anti-leakage protection device, without inductive electricity and leakage
18. The control circuit board adopts high-end integrated intelligent identification chipset, limit switch double protection, stability, safety and reliability

► Specification:

Touch screen	support touch
Lifting time	8S
Elevation angle	0-30°, fully in line with ergonomic principles, without blocking sight and face
Environmental conditions	-20°C~50°C, relative humidity ≤70%
Screen size	15.6"
Screen ratio	16:9
Screen resolution	1920*1080
Video interface	1 VGA, 1 HDMI; support central control switching
Control interface	2 network ports to control the display screen up and down, 1 USB port for power on/off, 2 USB ports for data transmission
Panel interface	1 USB port (data transmission)
Panel size	615*50*3mm
Backlight type	WLED, 15K hours, including LED driver
Contrast 800	1 (Typ.) (TM)
Viewing angle	85/85/85/85 (Typ.)(CR≥10)
Light source type	10S4P WLED, 15K hours, including LED driver
Display thickness	8.0mm
Back screen size	10.1 inches
Contrast ratio	800 : 1 (Typ.) [Transmission]
Backlight type	WLED, 15K hours, including LED driver
Viewing angle	85/85/85/85 (Typ.)(CR≥10)
Power supply	12v
Power consumption	60W
Microphone	
Frequency response	80Hz-16KHz
Microphone input impedance	1KΩ
Sensitivity	-46dBV/Pa
Maximum SPL1	25dB (A)
Signal-to-noise ratio	>80dB
THD	<0.1%
Power consumption	3W