

Gooseneck Wireless Conference Unit KRU-WE430



Feature:

- 1. Based on original digital audio processing and transmission technology
- 2. Gooseneck microphone design, high sensitivity, high-end and solemn appearance
- 3. Equipped with microphone speaking switch with indicator light
- 4. Built-in 4.3-inch 320*480 resolution TFT LCD capacitive touch screen, dynamic clock interface, support system information, call service, water filling and other menu content settings
- 5. Made of zinc/aluminum alloy, anodized process, CNC precision processing
- 6. Simple and elegant tabletop structure, ergonomic and modern
- 7. Customized chairman configuration function, according to the needs of the site, any unit can be temporarily defined as the chairman unit, and the chairman unit has the priority to close the representative unit's speech
- 8. Wireless transmission technology, using 128-bit AES encryption technology, supports WPA/WPA2 wireless security technology, prevents eavesdropping and unauthorized access, and provides higher confidentiality of the conference system
- 9. It has intelligent fault detection function to prompt AP connection status
- 10. Cooperate with PC digital conference system management software to realize functions such as sign-in, voting, election, rating, and custom two/three/four/five items
- 11. The unit can be voice-controlled and sensitivity adjusted through PC software
- 12. The overall control of speech can be performed through PC software, with timed speech and timed speech functions
- 13. Supports speech timing, signal strength, battery power and other information to be clearly displayed
- 14. The unit can adjust the 5-band EQ function through software to adjust different sound effects to meet the voice characteristics of different speakers
- 15. Sign-in can be initiated through PC software, and control unit sign-in and other functions can be controlled



Gooseneck Wireless Conference Unit KRU-WE430

Specification:

Frequency response	20Hz-20KHz
Signal-to-noise ratio	>78dB
Dynamic range	>108dB (1KHz)
Total harmonic distortion	<0.05%
Maximum power consumption	1.5W
Crosstalk	>70dB
Battery capacity	5000mAh
Screen	4.3-inch TFT LCD capacitive touch screen
Screen resolution	320*480
Shell material	zinc/aluminum alloy + ABS
Wireless frequency range	5.15GHz~5.85GHz
Charging method	through TYPE-C interface, support 18W fast charging
Color	black
Size (length * width * height mm)	base 128*98*58