



Product Features

1. The overall high-end and solemn, beautiful appearance design, in line with modern aesthetic standards
2. Professional high-fidelity capacitor 14mm microphone core, sensitive sound pickup, clear voice
3. Anti-interference circuit design, can prevent interference from mobile phones and other electronic products
4. The microphone has a speaking indicator light, which shows the unit speaking or off status
5. The unit is a passive device, powered by the system host, the voltage is DC24V, which is within the safe range
6. 2.4-inch TFT color LCD display can display ID addressing number, time, speaking timer and other information
7. The chairman unit can be installed arbitrarily without position restrictions when connected, and has the priority function of fully controlling the order of the meeting
8. Hand-in-hand connection mode, easy to install and maintain

Specifications

Frequency response	20Hz-20KHz	Total harmonic distortion	<0.05%
Sensitivity	-46dBV/Pa	Signal-to-noise ratio	>80dB
Equivalent noise	20dBA (SPL)	Maximum sound pressure level	125dB (THD<5%)
Input impedance	2kΩ	Directivity	cardioid
Base size	100 width × 134 depth × 57 height mm		
Mic rod size	360mm long; Mic head diameter 26mm		
Display	2.4-inch TFT color display; resolution 240x320		
Output wiring	comes with 1.1m eight-core female outlet		