



Product Features

1. The overall high-end and solemn double-pole, beautiful appearance design, in line with modern aesthetic standards
2. Professional high-fidelity capacitor 14mm microphone core, sensitive sound pickup, clear voice
3. Anti-interference circuit design, can prevent interference from mobile phones and other electronic products
4. The microphone has a speaking indicator light, which shows the speaking or off status of the unit
5. The unit is a passive device, powered by the system host, the voltage is DC24V, which is within the safe range
6. 2.4-inch TFT color LCD display can display ID addressing number, time, speaking timer and other information
7. The chairman unit can be installed arbitrarily without position restrictions when connected, and has the priority function of fully controlling the order of the meeting
8. Hand-in-hand connection mode, easy to install and maintain

Specifications

| | | | |
|-----------------------------|--|------------------------------|-----------------|
| Frequency response | 20Hz-20KHz | Total harmonic distortion | <0.05% |
| Sensitivity | -46 dBV/Pa | Signal-to-noise ratio | >80dB |
| Equivalent noise | 20 dBA (SPL) | Maximum sound pressure level | 125 dB (THD<5%) |
| Input impedance | 2 kΩ | Directivity | cardioid |
| Base size | 100 width × 134 depth × 57 height mm (excluding the shaft) | | |
| Display | 2.4-inch TFT color display; resolution 240x320 | | |
| Output wiring | comes with 1.1-meter eight-core female outlet | | |
| Single microphone pole size | 220 length × 33 width × 25 height mm | | |